

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: LogoClean

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Solvent-based cleaner

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier Logopak Systeme GmbH & Co. KG
Dorfstr. 40
24628 Hartenholm

Telephone: +49 (0)4195 / 99750
Fax: +49 (0)4195 / 1265

Contact Person:
E-mail: info@logopak.de

1.4 Emergency telephone number: +49 (0)6131 / 19240 (Giftinformationszentrum Mainz)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable liquids Category 2 H225: Highly flammable liquid and vapour.

Health Hazards

Serious eye irritation Category 2 H319: Causes serious eye irritation.

Specific Target Organ Toxicity -
Single Exposure Category 3 H336: May cause drowsiness or dizziness.

Aspiration Hazard Category 1 H304: May be fatal if swallowed and enters
airways.

Environmental Hazards

Chronic hazards to the aquatic
environment Category 3 H412: Harmful to aquatic life with long lasting
effects.

Hazard summary

Physical Hazards: Can form flammable vapour-air mixtures during the application.

Product name: LogoClean

Health Hazards

- Inhalation:** Has a narcotic effect.
- Skin Contact:** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
- Ingestion:** If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

2.2 Label Elements

Contains: Isopropyl alcohol
Hydrocarbons, low viscosity



Signal Words: Danger

Hazard Statement(s): H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H412: Harmful to aquatic life with long lasting effects.

Precautionary Statements

- General information:** P102: Keep out of reach of children.
- Prevention:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
- Response:** P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
- Disposal:** P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Supplemental label information

EUH066: Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Product name: LogoClean

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture based on volatile aromatic-free hydrocarbons and additives.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
Ethanol	EINECS: 200-578-6	20,00 - <50,00%	01-2119457610-43	
Hydrocarbons, low viscosity	EC: 927-241-2	25,00 - <50,00%	01-2119471843-32	
Isopropyl alcohol	EINECS: 200-661-7	20,00 - <50,00%	01-2119457558-25	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification
Ethanol	EINECS: 200-578-6	CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319
Hydrocarbons, low viscosity	EC: 927-241-2	CLP: Flam. Liq. 3;H226, Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 3;H412
Isopropyl alcohol	EINECS: 200-661-7	CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336

CLP: Regulation No. 1272/2008.

For the wording of the listed hazard statements refer to section 16.

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Skin Contact: Get medical attention if symptoms occur. Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash with water and soap; pay attention: skin degreasing product.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed: Causes serious eye irritation. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Headache.

Product name: LogoClean

- 4.3 Indication of any immediate medical attention and special treatment needed** Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

- General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
- 5.1 Extinguishing media**
- Suitable extinguishing media:** CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added
- Unsuitable extinguishing media:** Avoid water in straight hose stream; will scatter and spread fire.
- 5.2 Special hazards arising from the substance or mixture:** Can form explosive vapor-air mixtures at higher temperatures.
- 5.3 Advice for firefighters**
- Special fire fighting procedures:** Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
- Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. In case of spills, beware of slippery floors and surfaces. Keep away from sources of ignition - No smoking.
- 6.2 Environmental Precautions:** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Prevent from spreading (e.g. by binding or oil barriers). Environmental manager must be informed of all major spillages. Do not allow to enter drainage system, surface or ground water.
- 6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
- 6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

Product name: LogoClean

Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Avoid contact with eyes. Wash hands thoroughly after handling. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Use only in well-ventilated areas. Risk of vapor concentration on the floor and in low-lying areas. Prevent formation of aerosols. Observe good industrial hygiene practices. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities:

Store locked up. Store in a well-ventilated place. Store in a cool place. Local regulations concerning handling and storage of waterpolluting products have to be followed. The precautions for storing and handling of flammable liquids have to be kept. Local regulations for common storage of flammable liquids have to be followed.

7.3 Specific end use(s):

Not applicable

Storage Class:

3, Flammable Liquids

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Ethanol	TWA	1.000 ppm 1.920 mg/m3	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
Isopropyl alcohol	TWA	400 ppm 999 mg/m3	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
Isopropyl alcohol	STEL	500 ppm 1.250 mg/m3	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Product name: LogoClean

Eye/face protection:	Wear eye protection/face protection.
Skin protection	
Hand Protection:	Material: Nitrile-butadiene rubber (NBR). Min. Breakthrough time: ≥ 480 min Recommended thickness of the material: $\geq 0,38$ mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
Respiratory Protection:	Do not breathe dust/fume/gas/mist/vapours/spray. Provide adequate ventilation. In case of inadequate ventilation wear respiratory protection. Filter A/P2.
Thermal hazards:	Not known.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	liquid
Form:	Pump spray with sealed spray attachment
Color:	Colorless
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	Not applicable
Freezing point:	Not applicable for mixtures
Boiling Point:	80 °C
Flash Point:	12 °C (DIN EN ISO 2719)
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)-:	Not applicable for mixtures
Flammability Limit - Lower (%)-:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Vapor density (air=1):	Not applicable for mixtures
Density:	0,77 g/cm ³ (15 °C) (DIN 51757)
Solubility(ies)	

Product name: LogoClean

Solubility in Water:	partly soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Flow time	Value not relevant for classification
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	
Minimum ignition temperature:	> 300 °C (DIN 51794)

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Material is stable under normal conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Heat, sparks, flames.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	No data available.
Eye contact:	Causes eye irritation.

11.1 Information on toxicological effects

Acute toxicity

Oral

Product:	Not classified for acute toxicity based on available data.
Specified substance(s)	
Hydrocarbons, low viscosity	LD 50 (Rat): > 5.001 mg/kg (OECD 401)
Isopropyl alcohol	LD 50 (Rat): 4.570 mg/kg

Product name: LogoClean

Dermal

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Hydrocarbons, low viscosity

LD 50 (Rabbit): > 5.001 mg/kg (OECD 402)

Isopropyl alcohol

LD 50 (Rabbit): 13.400 mg/kg

Inhalation

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Isopropyl alcohol

LC 50 (Rat, 4 h): 30 mg/l

Skin Corrosion/Irritation:

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

Hydrocarbons, low viscosity

OECD 404
Prolonged or repeated contact:
Slightly irritating.

Serious Eye Damage/Eye Irritation:

Product:

Based on available data, the classification criteria are met.

Respiratory or Skin Sensitization:

Product:

Skin sensitizer: Based on available data, the classification criteria are not met.

Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

Hydrocarbons, low viscosity

No sensitizing effect (guinea pig); OECD 406

Germ Cell Mutagenicity

Product:

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product:

Based on available data, the classification criteria are met.

Specific Target Organ Toxicity - Repeated Exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration Hazard

Product:

May be fatal if swallowed and enters airways.

Other adverse effects:

No data available.

Product name: LogoClean

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Hydrocarbons, low viscosity LC 50 (Fish, 96 h): 10 - 30 mg/l

Isopropyl alcohol LC 50 (Fish, 96 h): 9.640 mg/l

Aquatic Invertebrates

Specified substance(s)

Hydrocarbons, low viscosity EC 50 (Water Flea, 48 h): 22 - 46 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are met.

Toxicity to Aquatic Plants

Specified substance(s)

Hydrocarbons, low viscosity EC 50 (Alga, 72 h): > 1.000 mg/l

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Specified substance(s)

Hydrocarbons, low viscosity 89 % (28 d) The product is easily biodegradable.

12.3 Bioaccumulative potential

Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

Harmful to aquatic life with long lasting effects.

Water Hazard Class (WGK):

WGK 1: slightly water-endangering.

Product name: LogoClean

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

15 01 10*: packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR/RID

14.1 UN Number: UN 1993
14.2 UN Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.(Ethanol, Isopropyl alcohol)
14.3 Transport Hazard Class(es)
Class: 3
Label(s): 3
Hazard No. (ADR): 33
Tunnel restriction code: (D/E)
14.4 Packing Group: II
14.5 Environmental hazards: –
14.6 Special precautions for user: –

ADN

14.1 UN Number: UN 1993
14.2 UN Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.(Ethanol, Isopropyl alcohol)
14.3 Transport Hazard Class(es)
Class: 3
Label(s): 3
14.3 Packing Group: II
14.5 Environmental hazards: –
14.6 Special precautions for user: –

IMDG

14.1 UN Number: UN 1993
14.2 UN Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.(Ethanol, Isopropyl alcohol)
14.3 Transport Hazard Class(es)
Class: 3
Label(s): 3
EmS No.: F-E, S-E
14.3 Packing Group: II
14.5 Environmental hazards: –
14.6 Special precautions for user: –

Product name: LogoClean

IATA

14.1 UN Number:	UN 1993
14.2 Proper Shipping Name:	Flammable liquid, n.o.s.(Ethanol, Isopropyl alcohol)
14.3 Transport Hazard Class(es):	
Class:	3
Label(s):	3
14.4 Packing Group:	II
14.5 Environmental hazards:	–
14.6 Special precautions for user:	–

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer: none

Regulation (EC) No. 850/2004 on persistent organic pollutants: none

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Other information: The classification complies with the current EU lists; however, it has been supplemented with expert literature information and information provided by/about our company. It was derived from the test data and/or the application of the conventional method.

Revision Date: 12.06.2018

Product name: LogoClean

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.